

# TYPE SGR

## INTERCONNECTION BATTERY CABLE



### Applications

Direct's Type SGR is a durable and versatile battery cable designed for interconnection between battery terminals and starters or grounds in automotive and other vehicular applications (e.g. car, bus, truck, tractor, etc.). Type SGR is UL listed, compliant to RoHS and SAE J1127 standards, and manufactured in the USA.

### Construction

- Rope-lay, bunch-stranded 30 AWG SAE copper conductor
- Wrapped paper separator
- Jacketed with proprietary LSHF EPDM compound

[See reverse for construction details and technical specifications](#)

TYPE SGR   INTERCONNECTION BATTERY CABLE						
AWG SIZE	# COND STRAND / DIAM (OR) GA	NOMINAL INSULATION THICKNESS		NOMINAL OUTSIDE DIAMETER (+JACKET)		APPROX LBS PER 1K'
		INCHES	MM	INCHES	MM	
#6	260 / 30	.060	1.52	.308	7.82	112
#4	364 / 30	.060	1.52	.343	8.71	149
#2	624 / 30	.060	1.52	.418	10.62	236
#1	767 / 30	.080	2.03	.488	12.40	306
1 / 0	975 / 30	.080	2.03	.533	13.54	371
2 / 0	1,196 / 30	.080	2.03	.568	14.43	450
3 / 0	1,547 / 30	.080	2.03	.618	15.70	567
4 / 0	1,950 / 30	.080	2.03	.688	17.48	708

All data and specifications contained herein are current and subject to change without notification. All values are nominal and/or approximate and may vary.

©2020 Direct Wire. All rights reserved.



# TYPE SGR BATTERY CABLE

## TECHNICAL SPECIFICATIONS

---

### Construction

---

- |                     |  |
|---------------------|--|
| Conductors          | <ul style="list-style-type: none"><li>Rope-lay, bunch-stranded 30 AWG SAE copper conductor</li></ul>   |
| Voltage Rating      | <ul style="list-style-type: none"><li>60 V DC; 25 V AC</li></ul>   |
| Insulation & Jacket | <ul style="list-style-type: none"><li>Wrapped paper separator</li><li>Jacketed with proprietary low-smoke, halogen-free EPDM compound</li><li>Resistant to abrasion, battery acid, diesel fuel, engine coolant, engine oil, ethanol, extreme temperatures, flame, gasoline, power-steering fluid, transmission fluid</li></ul> |
| Temperature Range   | <ul style="list-style-type: none"><li>-40°C (-40°F) to 105°C (221°F)</li></ul>   |
- 

### Standards & Certifications

---

- |                    |  |
|--------------------|--|
| Industry Approvals | <ul style="list-style-type: none"><li>UL 2556</li><li>Meets battery cable requirements per:<ul style="list-style-type: none"><li>UL 558 and UL 583</li><li>UL 4127 (60 V DC; 25 V AC)</li></ul></li><li>SAE J1127 Compliant</li><li>REACH, RoHS, CMRT, and Prop 65 Compliant</li></ul> |
|--------------------|--|
- 

### Standard Stock

---

- |                   |  |
|-------------------|--|
| Available Lengths | <ul style="list-style-type: none"><li>Coils/Assemblies at 25', 50', 100', and 250'</li><li>Reels at 500', 1,000', and 2,500'</li><li>Custom lengths available upon request</li></ul> |
|-------------------|--|
- 

### Customization

---

- |                       |  |
|-----------------------|--|
| Jacket Colors         | <ul style="list-style-type: none"><li><span style="display: inline-block; width: 10px; height: 10px; background-color: black; margin-right: 5px;"></span> Black <span style="display: inline-block; width: 10px; height: 10px; background-color: red; margin-left: 20px; margin-right: 5px;"></span> Red</li></ul> |
| Standard Print Legend | <ul style="list-style-type: none"><li>{AWG SIZE} SGR EXTRA FLEXIBLE BATTERY CABLE SAE J1127 -40°C +105°C MADE IN USA</li></ul>   |
| Marking Options       | <ul style="list-style-type: none"><li>Quick Print®; Surface Print; Indent Print; Logo/Icon; Sequential Marking</li></ul>   |