


CABLE LINE CARD

INDUSTRIAL & OEM



Direct Wire is widely recognized as a leading manufacturer of high-quality wire and cable solutions that conform to or exceed stringent US and international standards and specifications. Every day, we proudly manufacture industry-best products which offer superior physical, mechanical, and resistance properties required for demanding industrial and OEM applications.




3284 / CL1254

- 30 AWG ASTM Class K
- #6 – 4/0¹
- Paper Separator
- EPR Jacket
- -50°C – 125°C (3284)
- -30°C – 125°C (CL1254)
- 600 V
- ● / ●²
- UL 758, 1581, & 2556 / CSA C22.2 No. 127 & 2556 / ASTM B3, B33, B49, & B263 / cRUus / FT-1, FT-2, & VW-1 / REACH, RoHS, CMRT, & Prop 65




BOOSTER / DUPLEX

- 30 AWG SAE Copper
- #8 – 1/0 (2 Conductors)¹
- TPE Jacket
- SAE J1127 Type SGT / RoHS & Prop 65
- -50°C – 105°C
- 60 V
- ● / ● (Bridged)



3311 / 3279 / CL905

- 30 AWG ASTM Class K
- #8 – 250 MCM¹
- Paper Separator
- EPDM Jacket
- -50°C – 90°C / 105°C
- -30°C – 90°C (CL905)
- 600 V
- ● / ●²
- UL 758, 1581, & 2556 / CSA C22.2 No. 127 & 2556 / ASTM B3, B33, B49, & B172 / cRUus / FT-1, FT-2, & VW-1 / REACH, RoHS, CMRT, & Prop 65




DURA-FLEX® TYPE W

- 30 AWG ASTM Class K
- #6 – 4/0¹
- Paper & Mesh Separators
- EPDM (Inner) / CPE (Outer)
- UL 44, 1650, & 2556 / CSA 22.2 No. 96 & No. 2556 / ASTM B3, B49, & B172 / cULus / MSHA / FT-1, FT-2, & FT-5 / RHH/RHW/RHW-2 / RoHS & Prop 65
- -40°C – 90°C
- 600 V; 2,000 V
- ●²



ALL-FLEX®

- 30 AWG ASTM Class K
- #8 – 500 MCM¹
- PVC Jacket
- UL 758, 1232, 1283, 1284, 1337, 1338, 1339, 1426, 1581, 2556, 10070, & 10269 / UL 83 (THHW) & 1063 (MTW) / For CT Use / CSA C22.2 No. 75, 127-18, 210-15, & 2556 / ASTM B3, B33, B49, & B172 / SAE J1127 / ABYC E-11 / 33 CFR Sub. S / FT-1, FT-2, FT-4, & VW-1 / REACH, RoHS, CMRT, & Prop 65
- -50°C – 105°C
- 600 V; 1,000 V (AWM 10269)
- ● / ●²



FLEX-A-PRENE®


- 30 AWG SAE Copper
- #8 – 500 MCM¹
- Paper Separator
- EPDM Jacket
- SAE J1127 (#6 – 250 MCM) / NEC Article 630 / REACH, RoHS, CMRT, & Prop 65
- -50°C – 105°C
- 600 V
- ●²

All data and specifications are subject to change or correction without notification. All values are nominal and subject to manufacturing tolerances.

©2021 Direct Wire. All rights reserved.




CABLE LINE CARD INDUSTRIAL & OEM




SGR

- 30 AWG SAE Copper
- #6 – 4/0¹
- Paper Separator
- EPDM Jacket
- UL 2556 & 4127 / SAE J1127 / REACH, RoHS, CMRT, & Prop 65
- -40°C – 105°C
- 60 V DC; 25 V AC
- ● ●²



SOOW MSHA

- 30 AWG SAE Copper
- 8 – 2 AWG (2, 3, 4 Cond.)¹
- Paper Separators/Spacers
- EPDM (Inners) / CPE (Outer)
- UL 758, 1581, & 2556 / CSA C22.2 No. 127 & 2556 / ASTM B3, B33, B49, & B172 / cRUus / FT-1, FT-2, & VW-1 / REACH, RoHS, CMRT, & Prop 65
- -40°C – 90°C
- 600 V
- Color-coded Inners
- ●²




SGT

- SAE Copper
- #6 – 4/0¹
- PVC Jacket
- UL 2556 & 4127 (105°C) / SAE J1127 / REACH, RoHS, CMRT, & Prop 65
- -50°C – 80°C / 105°C
- 60 V DC; 25 V AC
- ● ●²




ULTRA-FLEX®

- 34/36 AWG SAE Copper
- #2 – 2/0¹
- TPE Jacket
- SAE J1127 / NEC Article 630 / RoHS & Prop 65
- -50°C – 105°C
- 600 V
- ● / ● (Jacket / Stripe)



SGX XLPO

- SAE Copper / ASTM Class K
- #6 – 250 MCM¹
- Paper Separator
- XLPO Cross-Linked Jacket
- SAE J1127 / REACH, RoHS, CMRT, & Prop 65
- -40°C – 125°C
- 60 V DC; 25 V AC
- ● ●²



VERI-FLEX® STAGE CABLE

- 30 AWG ASTM Class K
- #8 – 4/0¹
- Paper Separators
- EPDM (Inner) / CPE (Outer)
- UL 44, 1581, & 1680 / cULus / CSA 22.2 No. 96 & No. 2556 / ASTM B3, B49, B172, & B263 / NFPA 70; NEC Articles 400, 520, 525, & 530 / FT-5 & VW-1 / MSHA / RoHS & Prop 65
- -50°C – 105°C
- 600 V
- ●²

COLOR OPTIONS

- Black
- Blue
- Brown
- Green
- Orange
- Red
- White
- Yellow
- Custom

MARKING OPTIONS

- Quick Print®
- Surface Print
- Indent Print
- Stripe Color
- Sequential Footage

¹ = Denotes cable gauge/size range. Product availability is dependent on inventory stock levels at time of order. Manufacturing lead times may vary and minimum order quantities may apply for non-stocked gauges/sizes.

² = Denotes standard stock color(s). Product availability is dependent on inventory stock levels at time of order. Manufacturing lead times may vary and minimum order quantities may apply for non-standard and custom colors.

All specifications and standards are dependent on cable product style, including but not limited to, conductor size.

