



DIRECT WIRE



POWER

CABLE ASSEMBLIES

DURAFLEX® TYPE W POWER ASSEMBLIES



TYPE W W/M&F CAMS WITH STRAP COIL



TYPE W W/CAM & BARE COIL

OUR MOST POPULAR ASSEMBLIES

DESCRIPTION	GAUGE	LENGTH	PART NO.
4/0 TYPE W BLK 50' W/BLK M&F CAMS W/STRAP COIL	4/0	50	TW0161
4/0 TYPE W BLK 5' W/BLK M CAM & BARE COIL	4/0	5	TW0122
4/0 TYPE W BLK 5' W/BLK F CAM & BARE COIL	4/0	5	TW0123

ADDITIONAL TYPE W POWER ASSEMBLIES



TYPE W W/EDISON EXTENSION



TYPE W W/M&F CAMS & PIGTAILS



TYPE W W/PIN & SLEEVE

VERI-FLEX® STAGE CABLE ASSEMBLIES



TYPE SC 5-BANDED W/ CAMS & BARE COIL



TYPE SC 5-BANDED W/ M&F CAMS

OUR MOST POPULAR ASSEMBLIES

DESCRIPTION	GAUGE	LENGTH	PART NO.
#2 SC BLK 50' BANDED W/BLK, BLU, RED, GRN, WHT M&F CAMS W/ STRP	#2	50	SC0087
#2 SC BLK 5' BANDED W/BLK, BLU, RED, GRN, WHT M CAMS & BARE	#2	5	SC0893
#2 SC BLK 5' BANDED W/BLK, BLU, RED, GRN, WHT F CAMS & BARE	#2	5	SC0174

ADDITIONAL STAGE CABLE ASSEMBLIES



TYPE SC W/CAM-LOK FEEDER CABLE



TYPE SC W/STAGE PIN EXTENSION



TYPE SC W/PIGTAILS

S00W (MSHA) POWER ASSEMBLIES



S00W W/SPIDER BOX/CA. STANDARD CORD

OUR MOST POPULAR ASSEMBLIES

DESCRIPTION	GAUGE	LENGTH	PART NO.
4/0 TYPE W BLK 50' W/BLK M&F CAMS W/STRAP COIL	4/0	50	TW0161
4/0 TYPE W BLK 5' W/BLK M CAM & BARE COIL	4/0	5	TW0122

ADDITIONAL TYPE W POWER ASSEMBLIES



S00W W/TWIST-LOCK EDISON EXTENSION



S00W W/WET-GUARD WATERTIGHT EXTENSION



S00W W/STRAIGHT BLADE EDISON EXTENSION

POWER PACK

BULK POWER CABLE & ASSEMBLIES

Power Pack Product Configurations

- 4/0 Duraflex® Type W BLK 50' Bulk Power Pack (QTY 40 - M&F Cams)
- 4/0 Duraflex® Type W BLK 5' Tails Bulk Power Pack (QTY 100 - M Cam)
- 4/0 Duraflex® Type W BLK 5' Tails Bulk Power Pack (QTY 100 - F Cam)
- #2 Veri-flex® SC BLK 50' Banded Bulk Power Pack (QTY 15 - M&F Cams)
- #2 Veri-flex® SC BLK 5' Tails Banded Bulk Power Pack (QTY 50 - M Cam)
- #2 Veri-flex® SC BLK 5' Tails Banded Bulk Power Pack (QTY 50 - F Cam)
- 6/4 S00W MSHA BLK 50' Bulk Power Pack (QTY 40 - (50A 125/250V connectors))



CAM-LOCK

POWER CABLE CONNECTORS



Boot with Screw (Male & Female)



Specifications

- UV resistant Santoprene™
- Single-piece brass contacts
- Available in all gauges
- 400 A; 600 V

In-Line Cams (Male & Female)



Specifications

- UV resistant santoprene
- Brass contacts
- Available in all gauges
- -40°C to 105°C
- 400 A; 600 V



DIRECT WIRE
412 OAK STREET
DENVER, PA 17517
(800) 233-3848
sales@directwire.com
DIRECTWIRE.COM